

Technical Data - Datos técnicos

Undercarriage	Carro de orugas		
Wheel base	Distancia entre ejes	2.000 mm / 6,5 ft	
Max width	Ancho max	2.100 mm / 6,9 ft	
Pad width	Ancho zapata	400 mm / 15,7 in	
Max. climbing ability	Pendiente max	36 %	
Max. speed	Velocidad max	1,5 km/h / 0,93 mph	
Power pack	Grupo accionamiento		
Diesel engine	Motor diesel	DEUTZ TCD 2012 L04	
Engine power	Potencia motor	95 kW (129 HP) / 2.300 rpm	
Oil tank	Depósito de aceite	350 l / 92,5 gal	
Fuel tank	Depósito de combustible	150 l / 39,5 gal	
Mast	Mástil		
Feed stroke	Carrera útil	2.540 - 4.040 mm / 83,3 - 13,2 ft	
Total length	Largo total	4.260 - 5.760 mm / 13,9 - 18,8 ft	
Feed force	Fuerza de empuje	6.000 daN / 13,488 lbs	
Retract force	Fuerza de tiro	6.000 daN / 13,488 lbs	
Rotary head	Cabeza de rotación	R1300	R2400
Gears	Velocidades	6	3
Max torque	Par max	1.300 daNm / 9,588 lb*ft	2.400 daNm / 17,701 lb*ft
Max speed	Revoluciones max.	350 rpm	144 rpm
Head passage	Paso libre cabeza	92 mm / 3,6 in	116 mm / 4,5 in
Clamps	Mordazas		
Clamping range	Rango diámetros cierre	45 - 320 mm / 1,8 - 12,5 in	
Clamping force	Fuerza de cierre	230 KN / 51,706 lbs	
Breaking torque	Par de apriete	2.050 daNm / 15,120 lb*ft	
Weight	Peso	11.000 - 13.000 kg / 24,300 - 28,500 lbs	